



# Hewlett Packard Enterprise

Product Information Sheet:

## Lithium-Ion Rechargeable Batteries for HPE Products

### PURPOSE OF THIS DOCUMENT

Hewlett Packard Enterprise (“HPE”) is providing the information in this document voluntarily as a service to its customers. The products addressed in this document are generally viewed as “articles” that are exempt from requirements for Safety Data Sheets (“SDSs”) such as the Hazard Communication Standard of the U.S. Occupational Safety and Health Administration (“OSHA”) and similar requirements in other countries. In particular, these products are manufactured according to a specific design, have an end-use dependent upon such design, and do not normally release more than trace amounts of hazardous chemicals.

### PRODUCT IDENTIFICATION

The products covered by this document are lithium-ion rechargeable batteries originally contained in HPE-branded electronic products or otherwise provided by HPE for use in or with such electronic products.

Such batteries may be produced by a number of manufacturers. Information about individual battery types can be found in documents provided by the manufacturers, which HPE voluntarily makes available to the public on request. The manufacturers have assured HPE that they believe these documents are reliable as of the dates indicated in the documents. HPE has not conducted an independent assessment of the information in the documents.

The information in this document is based on documents provided by the battery manufacturers, and is intended to provide a generalized view of the information typically found in such documents. The information in this document is not intended to be, and should not be used as, a substitute for the information provided by the manufacturers. To the extent that a manufacturer’s information differs from any information in this document, the manufacturer’s information should govern.

### HAZARDS IDENTIFICATION

Under routine handling and use, there should be no known effects on eyes, skin, or inhalation. In the battery cell(s), chemical materials are stored in a sealed metal or metal laminated plastic case, designed to withstand temperatures and pressures encountered during normal handling and use. As a result, during normal handling and use, there is no significant physical danger of ignition, explosion, or exposure to materials of concern. However, if the battery is exposed to a fire, the battery may rupture violently, leading to the possible release of irritating gas.

## COMPOSITION

The composition of the lithium-ion batteries originally contained in HPE-branded electronic products (or otherwise provided by HPE for use in or with such products) may vary. The composition information below is intended to provide a generalized view of the constituents of lithium-ion batteries. For information on the composition of individual battery types, please see the information provided by the individual battery manufacturers.

| <b>Chemical</b>                                   | <b>CAS No.</b> | <b>Percent<br/>(Max.)</b> |
|---|----------------|---------------------------|
| Graphite  | 7782-42-5      | 30                        |
| Lithium cobalt oxide                              | 12190-79-3     | 50                        |
| Cobalt oxide                                      | 1307-96-6      | 50                        |
| Nickel oxide                                      | 1313-99-1      | 50                        |
| Manganese oxide                                   | 1313-13-9      | 50                        |
| Diethyl carbonate                                 | 105-58-8       | 15                        |
| Dimethyl carbonate                                | 616-38-6       | 15                        |
| Ethyl methyl carbonate                            | 623-53-0       | 15                        |
| Propylene carbonate                               | 108-32-7       | 15                        |
| Ethylene carbonate                                | 96-49-1        | 15                        |
| Polyvinylidene fluoride                           | 24937-79-9     | 10                        |
| Hexafluoropropylene-vinylidene fluoride copolymer | 9011-17-0      | 15                        |
| Lithium hexafluorophosphate                       | 21324-40-3     | 5                         |
| Aluminum  | 7429-90-5      | 10                        |
| Copper  | 7440-50-8      | 15                        |
| Nickel  | 7440-02-0      | 15                        |
| Styrene butadiene rubber                          | 9003-55-8      | 5                         |
| Iron  | 7439-89-6      | 25                        |
| Manganese   | 7439-96-5      | 15                        |
| Acetylene black (carbon black)                    | 133-86-4       | 2                         |

The constituents above are listed in one or all of the lithium-ion battery documents provided by the manufacturers, at concentrations up to the levels indicated in the last column of the table. Some of the manufacturer documents also list “transition metal oxides” (at concentrations up to 50%) and/or “organic solvent”/“organic electrolyte” (at concentrations up to 20%) as battery constituents. These general categories are not included in the table above, because they may be intended to encompass some of the individual chemicals already in the table (e.g. “transition metal oxides” may refer to the oxides of cobalt, nickel, and/or manganese). Similarly, some manufacturer documents list “plastic” (at concentrations up to 4%), but this is not listed in the table because the specific plastics are not identified by the manufacturers and the material seems unlikely to be of regulatory concern. The information in the table above is based on the composition of the lithium-ion battery cells only, and does not reflect the constituents in other parts of a lithium-ion battery pack, such as the outer casing or printed circuit board.

Although the chemicals above are identified in documents provided by the manufacturers, HPE believes that other compounds containing lithium, metals, and/or carbon may be present, particularly in used batteries, due to chemical reactions that take place within the batteries, especially during use.

## FIRST AID MEASURES

Intact batteries do not represent a danger to health. If outer casing is damaged and exposure to internal materials results, the following first-aid actions are recommended:

- In response to inhalation: leave area immediately and seek medical attention.
- In response to eye contact: rinse eyes with water for fifteen minutes and seek medical attention.
- In response to skin contact: wash area thoroughly with soap and water and seek medical attention.
- In response to ingestion: induce vomiting and seek medical attention.

## FIRE FIGHTING MEASURES

Use suitable extinguishing media for the materials that are burning such as: chemical powder fire extinguishing medium, fire foam, carbon dioxide gas, nitrogen gas, dry sand, or water in large amounts. Water may react with available lithium or electrolyte in the batteries producing flammable hydrogen or hydrofluoric acid. When fighting fire, wear a self-contained breathing apparatus and protective suit. If possible, remove cells from firefighting area; if heated excessively, cells may rupture violently or vent irritating gas.

## ACCIDENTAL RELEASE MEASURES

- Personal precautions: use personal protective clothing; avoid contact with skin, eyes, and clothing; avoid breathing fumes.
- Environmental precautions: do not discharge into the drains/surface waters/groundwater; place spilled materials into appropriate container and dispose of properly.

## HANDLING AND STORAGE

- Advice on safe handling: Avoid short-circuiting the cell. Do not open or disassemble. Keep away from open flames, hot surfaces, and sources of ignition.
- Advice on storage: Store at room temperature at approximately 20%-60% of the normal battery capacity. Keep in appropriate packaging.

## EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protective equipment is not required for handling intact cells. In response to ruptured cells, use the following equipment: respirator with air cylinder and dust mask; protective gloves; goggles or protective glasses designed to protect against liquid splashes; working clothes with long sleeves and long pants.

## PHYSICAL AND CHEMICAL PROPERTIES

|                      |           |
|----------------------|-----------|
| Form                 | Solid     |
| Color                | Various   |
| Odor                 | Odorless  |
| pH                   | n/a       |
| Flash point          | n/a       |
| Vapor pressure       | n/a       |
| Density              | n/a       |
| Water solubility     | Insoluble |
| Ignition temperature | n/a       |

## STABILITY AND REACTIVITY

- **Stability:** stable under normal handling and use. If cell is ruptured, hazardous decomposition products may form.
- **Conditions to avoid:** keep away from open flames, direct sunlight, and high humidity. Avoid contact of battery with water, strong oxidizers, and strong acids.

## TOXICOLOGICAL INFORMATION

Routine handling and use of this product does not result in significant exposure to substances of toxicological concern.

## ECOLOGICAL INFORMATION

To avoid improper exposure to environment, battery should be disposed of per the “Disposal Considerations” guidance below.

## DISPOSAL CONSIDERATIONS

Do not incinerate. Lithium-ion rechargeable batteries should be disposed of or recycled in accordance with any applicable national, state/provincial, and local requirements. HPE encourages the environmentally sound recycling of these products. Please contact HPE for additional information on [recycling](#) our used lithium-ion batteries.

## TRANSPORTATION

Lithium-ion batteries are generally classified for purposes of transportation as UN 3480/3481. However, the lithium-ion batteries originally contained in HPE-branded electronic products (or otherwise provided by HPE for use in or with such electronic products) may be of a type that allows the batteries to be excepted from requirements for transport as Class 9 hazardous materials or dangerous goods under most national and international regulations. The majority of batteries have a Watt-hour rating of no more than 20 WH per cell or no more than 100 WH per battery pack and contain “equivalent lithium” in amounts no more than 1.5 g per cell or 8.0 g per battery pack. Batteries that exceed the aforementioned limitations generally must be packed and shipped under full class 9 regulations. In addition, the batteries are of a type that has been demonstrated to pass each applicable test (T.1 through T.8) under the UN Manual of Tests and Criteria (ST/SG/AC.10/11/Rev.6/Amend.1), Part III, Subsection 38.3.

To qualify for exception, the batteries may be subject to certain requirements relating to packaging, marking, shipping documentation, quantity limitations, and the like. For example, under the Dangerous Goods Regulations ([65th Edition, 2024](#)) of the International Air Transport Association (“IATA”), excepted lithium-ion batteries must be transported in accordance with the requirements of Section IB of Packing Instruction 965 (or Section II of Packing Instruction 966 or 967, for batteries packed with or contained in equipment, respectively). See also, e.g., 49 C.F.R. § 173.185(c); Special Provision 34 of the Canadian Transport of Dangerous Goods Regulations.

*Under IATA Special Provision A154 and Packing Instruction 965, recalled or damaged lithium batteries are generally prohibited from air transportation.*

## INITIAL BATTERY CHARGE LEVEL

Lithium-ion batteries are shipped from the factory at a state of charge (SoC) below 30%. IATA requirements specify a SoC not to exceed 30% for air shipments of batteries without equipment, unless special approval is obtained from the authorities in relevant countries. See IATA Special Provision A331 and Packing Instruction 965.

## DISCLAIMER

This document is provided without charge to customers of HPE and its subsidiaries. It is based on information provided to HPE by the independent manufacturers of the products. HPE has not independently assessed the information provided by the manufacturers, and neither endorses nor guarantees the accuracy or completeness of any of the information contained herein. This document should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application.

## ISSUE DATE

This document was issued in [Feb 2024](#).